

Powersonic PS-12120L-FP 12V 12.0AH Battery



Powersonic PS-12120L-FP 12V 12.0AH Battery

1-11 \$49.92

12-49 \$42.79

50-99 \$39.93

Contact us for quantity pricing over 100 pcs.

Powersonic PS-12120L 12V 12.0AH Battery

Terminals:
FP: Positive: 0.250"
x 0.032", Negative:
0.187" x 0.032".
Mate with AMP. INC
FASTON "250/187"
series

Nominal Voltage12 volts (6 cells)
Nominal Capacity
20-hr. (600mA to 10.50 volts) 12.0 AH

10-hr. (1.19A to 10.50 volts) 11.9 AH
 5-hr. (2.21A to 10.20 volts) 11.1 AH
 1-hr. (8A to 9.00 volts) 8.00 AH
 15-min. (25.5A to 9.00 volts) 6.38 AH
 Approximate Weight 8.80 lbs. (3.99 kg)
 Energy Density (20-hr. rate) 1.08 W-h/in³ (65.77 W-h/l)
 Specific Energy (20-hr. rate) 16.36 W-h/lb (36.08 W-h/kg)
 Internal Resistance (approx.) 25 milliohms
 Max Discharge Current (7 Min.) 36.0 amperes
 Max Short-Duration Discharge Current (10 Sec.) 50.0 amperes
 Shelf Life (% of nominal capacity at 68°F (20°C))
 1 Month 97%
 3 Months 91%
 6 Months 83%
 Operating Temperature Range
 Charge .. -4°F (-20°C) to 122°F (50°C)
 Discharge -40°F (-40°C) to 140°F (60°C)
 Case ABS Plastic
 Power-Sonic Chargers PSC-122000A, 122000A-C

Batteries do not qualify for free freight promotion